


Fig. 1



2/13

Fig. 2





Fig. 3



3/13

Fig. 4





Fig. 5



4/13

Fig. 6





Fig. 7



5/13

Fig. 8






Fig. 9




6/13

Fig. 10A




7/13

Fig. 10B




8/13

Fig. 11A



9/13

Fig. 11B



10/13

Fig. 12

The figure displays three windows illustrating the interaction between a mobile device (running mfchen4iproxy) and a server (running PhoneServer and tnameserv.exe).

Top Window (Instant Message):

- Title bar: mfchen4iproxy - Instant Message
- Menu bar: File Edit View People
- Text area:

```
mingfengchen: corba exec PhoneDivert:getDivert herman herpass
mfchen4iproxy: ServerName=PhoneServant of herman
DriveNumber=4
Divt1:no=1,ring=3,phon=+886229505401,desc=Office Phone
Divt2:no=2,ring=6,phon=+886936105401,desc=Mobile Phone
Divt3:no=3,ring=5,phon=+889228734065,desc=Home
Divt4:no=4,ring=2,phon=+889229508655,desc=Audix
```
- Toolbar: A, B, I, U, Ink
- Buttons: Warn, BLOCK, Add Buddy, Info, Send

Middle Window (PhoneServer Log):


```
[c:\iproxy\corba]\jdk1.3\bin\java PhoneServer
Init ORB ...
Resolve NameService ...
PhoneServer ready ...
::getDivert < herman, xxx >
```

Bottom Window (tnameserv.exe Log):

```
[c:\jdk1.3\bin]tnameserv.exe
Initial Naming Context:
I OR:00000000000000284944c3a6f6d672e6f72672f436f734e61d69
6e746578743a312e3000000000001000000000000005400010100000000e
2e35320000f4000000018afabfce000000000029d66b7510000000000000e
000100000014000000000010020000000000001010000000000
TransientNameServer: setting port for initialobject reference tp: 908
Ready.
```

11/13

Fig. 13



12/13

Fig. 14




Fig. 15

13/13




Fig. 16

